

Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or design registrations. 除非经书面授权, 否则禁止转让、复制、利用、交流和文件附注等。侵犯者将承担赔偿责任。本公司保留对涉及发明、实用新型和外观设计的所有权利。

客户图 Drawings for customers		未注公差参照/General tolerances according to(mm): ISO2768-1 C									
		>0.5~3	> 3~6	> 6~30	> 30~120	> 120~400	>400~1000	>1000~2000	>2000~4000		
		±0.2	±0.3	±0.5	±0.8	±1.2	±2	±3	±4		
名称 Name	2芯280插头总成CodeA 2PIN280 Plug Assy-CodeA		2芯280插头总成CodeB 2PIN280 Plug Assy-CodeB		2芯280插头总成CodeC 2PIN280 Plug Assy-CodeC		2芯280插头总成CodeD 2PIN280 Plug Assy-CodeD		2芯280插头总成CodeE 2PIN280 Plug Assy-CodeE		
键位 Code	A		B		C		D		E		
键位示意图 Differernt code view											
对插型号 Matching type	DBYR-02A28-CXX (2芯280-插座总成 CodeA)		DBYR-02B28-CXX (2芯280-插座总成 CodeB)		DBYR-02C28-CXX (2芯280-插座总成 CodeC)		DBYR-02D28-CXX (2芯280-插座总成 CodeD)		DBYR-02E28-CXX (2芯280-插座总成 CodeE)		
产品图 product view 技术要求 Technical specification: 1、性能参数 Performance parameter: a、工作温度 Temperature Range: -40℃~125℃ b、额定工作电压 Working Voltage: 1000V DC c、额定工作电流 Current Capability: 16A Max@2.5mm² 24A Max@4mm² d、工作海拔 Altitude: 5000M e、绝缘电阻 Insulation resistance: >200MΩ 1000V DC f、耐电压 Withstand voltage: <5mA 1min 3000V AC g、防护等级 Class of protection: IP68、IP6K9K、IPXXB 2、法律法规 Laws and regulations ★a、产品符合阻燃要求; a、The product meets the flame retardant requirements ★b、环保要求: RoHS 2.0. b、Environmental protection requirement: RoHS 2.0.											
							材料/MATERIAL: /		表面效果/SURFACE: /		
							料号/PN: 26040000011		样品状态/MAT STATUS: /		
					批准/APPD 梁东 2024-06-15		名称/NAME: 2芯280插头总成 2PIN280 Plug Assy				
					审核/CHKD 李京乐 2024-06-15						
					制图/DRFT 陈自发 2024-06-15		版本/REV 00		类型/TYPE 客户图纸/Customr drawing		
									图纸状态/DRAWING STATUS /		
									比例/SCALE 1:1		
									页数/SHEET 1/2		

Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or design registrations. 除非经书面授权, 否则禁止转让、复制、利用、交流和文件附注等。侵犯者将承担法律责任。 采用新设计时, 请务必保留所有权利。

客户图 Drawings for customers																				
DBYS-02E28-C04 26040000230	4mm ² 、CodeE、 Shielded connector	1	-	-	-	-	1	2	-	2	-	2	-	1	-	1	7.00±0.20			
DBYS-02D28-C04 26040000226	4mm ² 、CodeD、 Shielded connector	1	-	-	-	1	-	2	-	2	-	2	-	1	-	1	7.00±0.20			
DBYS-02C28-C04 26040000222	4mm ² 、CodeC、 Shielded connector	1	-	-	1	-	-	2	-	2	-	2	-	1	-	1	7.00±0.20			
DBYS-02B28-C04 26040000218	4mm ² 、CodeB、 Shielded connector	1	-	1	-	-	-	2	-	2	-	2	-	1	-	1	7.00±0.20			
DBYS-02A28-C04 26040000002	4mm ² 、CodeA、 Shielded connector	1	1	-	-	-	-	2	-	2	-	2	-	1	-	1	7.00±0.20			
DBYS-02E28-C03 26040000228	2.5mm ² 、CodeE、 Shielded connector	1	-	-	-	-	1	2	2	-	2	-	1	-	1	-	5.80±0.20			
DBYS-02D28-C03 26040000224	2.5mm ² 、CodeD、 Shielded connector	1	-	-	-	1	-	2	2	-	2	-	1	-	1	-	5.80±0.20			
DBYS-02C28-C03 26040000220	2.5mm ² 、CodeC、 Shielded connector	1	-	-	1	-	-	2	2	-	2	-	1	-	1	-	5.80±0.20			
DBYS-02B28-C03 26040000216	2.5mm ² 、CodeB、 Shielded connector	1	-	1	-	-	-	2	2	-	2	-	1	-	1	-	5.80±0.20			
DBYS-02A28-C03 26040000011	2.5mm ² 、CodeA、 Shielded connector	1	1	-	-	-	-	2	2	-	2	-	1	-	1	-	5.80±0.20			
型号/料号 Type /PN	物料描述 Product description	26040000327	26040000248	26040000250	26040000252	26040000254	26040000256	26040000324	26040000322	26040000323	26040000320	26040000321	26040000319	26040000318	26040000316	26040000317	适用线缆外径 Applicable cable diameter (mm)	备注 Note		
		插头防尘盖 Plug dust cover	CodeA	CodeB	CodeC	CodeD	CodeE	母端子 Female terminal	2.5sqmm	4sqmm	2.5sqmm	4sqmm	2.5sqmm	4sqmm	2.5sqmm	4sqmm				
	子零件BOM Component BOM		插头壳体组件 Plug Housing Assy						屏蔽外环 Outer Ferrule		屏蔽内环 Inner Ferrule		线缆密封圈 Cable Seal		尾盖 Cap					
		No. 1	No. 2					No. 3	No. 4		No. 5		No. 6		No. 7					
</																				