



未注公差/General tolerances(mm)														0.1/10 ±2'
0 ~ 3	>3 ~ 6	>6 ~ 10	>10 ~ 18	>18 ~ 30	>30 ~ 50	>50 ~ 80	>80 ~ 120	>120 ~ 180	>180 ~ 250	>250 ~ 315	>315 ~ 400	>400 ~ 500	>500	
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50	



A

A




B

B

C

C



IEC 标准/IEC Standard:	
螺丝扭矩/Torque Tightening(N·m/Lb.in)	M2.5, 0.4/3.54
线径范围(硬线和软线)/Wire Range(rigid and flexible)(mm²/AWG)	0.2~2.5/26~12
间距/Pitch(mm)	5.10
剥线长度/Stripping length(mm)	8~9
使用温度范围/Operating temperature(°C)	-40~+105
符合RoHS环保要求/Conform to RoHS	Yes

MATERIAL: /		SURFACE: /	
MAT NO.: /		 宁波高松电子有限公司 NINGBO DEGSON ELECTRICAL CO., LTD	
STATUS: /			
APPD: Li GL 2020.05.27		NAME: DC2.5-PE-01P-1C-00A(H)	
CHKD: Mao J 2020.05.27			
DRFT: XMY 2016.01.29		DRAWING NO.: DC2.5-PE-C01	
 SIZE: A4 		TYPE: CUSTOMER DRAWING	SCALE: 2:1
		SHEET	1/1

5	Grounding	Copper alloy	Sn Plated
4	Cage	Steel	Zn Plated
3	Current Carrier	Copper	Sn Plated
2	Screw	Steel	Zn Plated
1	Housing	PA66	UL94 V-0
ITEM	NAME OF PART	MATERIAL	NOTES

REV	ECN	DESCRIPTION	DRFT	DATE
-----	-----	-------------	------	------