




未注公差/General tolerances(mm)

0 ~ 3	>3 ~ 6	>6 ~ 10	>10 ~ 18	>18 ~ 30	>30 ~ 50	>50 ~ 80	>80 ~ 120	>120 ~ 180	>180 ~ 250	>250 ~ 315	>315 ~ 400	>400 ~ 500	>500	0.1/10 ±2'
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50	



REV	ECN	DESCRIPTION	DRFT	DATE

3	Current carrier	Copper	Sn Plated
2	Spring	Stainless steel	
1	Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES
UL 标准/UL Standard:		B	C
额定电压/电流/Rated Voltage(V)/Current(A)		600/20	600/20
IEC 标准/IEC Standard:		D	
过压类别/Overvoltage Category/污染等级/ Pollution Degree		III/3	/
额定电压/电流/Rated Voltage(V)/Current(A)		800/32	/
额定脉冲电压(KV)/Rate Impulse Voltage(KV)		8	/
线径范围(硬线和软线)/Wire Range(rigid and flexible)(mm ² /AWG)		0.2~4.0/28~12	
间距/Pitch(mm)		6.2	
剥线长度/Stripping length(mm)		10~11	
使用温度范围/Operating temperature(°C)		-40~+105	
符合RoHS环保要求/Conform to RoHS		Yes	

MATERIAL: /		SURFACE: /	
MAT NO.: /		DEGSON[®] 宁波高松电子有限公司 NINGBO DEGSON ELECTRICAL CO., LTD	
STATUS: /			
APPD: Li GL 2020.05.29		NAME:	
CHKD: Mao J 2020.05.29		WS4-01P-1Y-100A(H)	
DRFT: LuoXM 2020.03.23		DRAWING NO.: WS4-C10	
SIZE: A4		TYPE: CUSTOMER DRAWING	
		SCALE: 2:1	
		SHEET 1/1	
		REV T0	