

LM514 Wi-Fi 6 (802.11ax) and Bluetooth® 5.2 Industrial M.2 Card

PCIe + USB Interface, M.2 2230 (A-E Key) Form Factor

Revised

Product Brief Version

09/FEB/2024

1.2



Features

- Wi-Fi 6 (802.11 a/b/g/n/ac/ax)
- Bluetooth® 5.2
(Backwards compatible with all previous Bluetooth versions)
- WPA, WPA2, WPA3, 802.1x and WEP (64bit & 128bit) encryption schemes
- MU-MIMO and data rate up to 1201Mbps
- Dual Mode simultaneous LE and BR/EDR support
- PCIe Interface for Wi-Fi, USB Interface for Bluetooth
- Operating temperature: -30°C to +85°C
- Supports Bluetooth adaptive power management
- 2.4~2.484 GHz and 5.0~5.8 GHz
- M.2 2230 (A-E) Key form factor
- 2 x IPEX connector receptacle
- 30mm x 22mm x 2.25mm
- Linux and Windows 10 – 11 compatible
- See the website for this product's certifications. RoHS, REACH and WEEE compliant

Overview

The LM514 module is a high-performance and highly integrated Wi-Fi 6 solution that offers coexistence for Bluetooth® Dual Mode and Wi-Fi operations, allowing the host computer to wirelessly communicate with other Bluetooth and Wi-Fi enabled devices.

The LM514 is ideal for industrial applications, delivering both high throughput and low power consumption. The compact form factor saves valuable space within your product, making it ideal for laptops, desktops, medical devices and industrial PCs.

The LM514 supports IEEE 802.11a/b/g/n/ac/ax and Bluetooth 2.0, 2.1, 3.0, 4.0, 4.2 and 5.2 standards and is compatible with Linux (Kernel 5.4), Windows 10 – 11 platforms.

*Please contact our sales team for further information.

LM514 Wi-Fi 802.11ax and Bluetooth® 5.2 M.2 Card

PCIe + USB Interface, M.2 2330 (A-E Key) Form Factor

General Specification

Wireless Standard	Wi-Fi: 802.11 a/b/g/n/ac/ax Bluetooth: 2.1+EDR/3.0/4.0/4.2/5.2 - BR/EDR and Low Energy
Module Type	M.2 Card
OS Compatibility	Linux, Windows 10 – 11
Security	Wi-Fi: WPA, WPA2, WPA3 , WEP (64bit & 128bit), TKIP, AES, 802.1x Bluetooth: Secure Simple Paring
Chipset	Realtek
Antenna	2 x IPEX Connectors
Interfaces	Wi-Fi: PCIe, Bluetooth: USB 2.0
Tx Output Power	Wi-Fi: 24GHz 17 dBm – 802.11b@11Mbps 15 dBm – 802.11g@54Mbps 14 dBm – 802.11n@MCS7_HT20 14 dBm – 802.11n@MCS11_HT40 5GHz 14 dBm – 802.11a@54Mbps 13 dBm – 802.11n@MCS7_HT20 12 dBm – 802.11n@MCS7_HT40 12 dBm – 802.11ac@MCS8_VHT20 11 dBm – 802.11ac@MCS9_VHT40 11 dBm – 802.11ac@MCS9_VHT80 12 dBm – 802.11ax@MCS11_HE20 11 dBm – 802.11ax@MCS11_HE40 Bluetooth: Typical 6 dBm
Frequency	24~2484 GHz , 5.0~5.8 GHz



LM514 Wi-Fi 802.11ax and Bluetooth® 5.2 M.2 Card

PCIe + USB Interface, M.2 2330 (A-E Key) Form Factor

General Specification (Continued)

Physical Characteristics

Operating Temperature	-30°C to +85°C ambient temperature 5 to 90 % (non-condensing)
Storage Temperature	-40°C to +90°C ambient temperature 5 to 90 % (non-condensing)
Dimensions (L x W x H)	25mm x 12mm x 2.25mm
Weight	TBA
Certifications	See the website for this product's certifications.
Compliance	RoHS, REACH and WEEE

DISCLAIMER

LM Technologies provides this document 'as is', without warranty of any kind. It is the responsibility of the customer to ensure that this product is fit for purpose. LM Technologies may make updates and/or changes to this document or to the product described in this document at any time. This document could include technical inaccuracies or typographical errors.

Though every effort has been made to ensure that this document is current and accurate, additional information may have become available subsequent to the production of this guide. Please consult with LM Technologies for the latest information regarding this product.